

# TRAC FARM PLUS - Technical Specifications



## Description

TRAC FARM PLUS is a rear tractor tire specifically designed for soil tillage and haulage applications. The tire features a deeper tread with dual angle lugs to ensure both excellent traction and a comfortable ride on the road. The special tread design provides more contact for better stability and great self-cleaning properties. TRAC FARM PLUS ensures a longer tire life-cycle.

## UM

US Standard

## Construction

 BIAS

## Machinery

Agriculture: Tractor

Version	STANDARD
Type	TT
Tyre Size	13.6 - 28
LI/SS	124 A8

## Dimensions US Standard

Usa code	94045686
Ply Rating	12
Section Width (inch)	14.4
Overall Diameter (inch)	53
Static Loaded Radius (inch)	24.4
Rolling Circumference (inch)	160.9
Rim Rec	W 12
Rim Alt	W 11
ECE	E11-106R-004527
TRA Code	R1

## Load capacity (lbs)

mph / psi	34
25	3530

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 7:49 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..