

TRAC SUPER - Data Sheet



Description

TRAC SUPER is the first radial tire introduced in BKT's municipality segment. The steel-belted tire structure ensures an excellent smooth drive combined with best traction performance. As a result, it is particularly suitable for applications on large lawn surfaces such as parks and roadsides.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Small Tractor

| SIZE | Version | LI/SS | RIM REC | RIM ALT | SW | OD | SLR | RC | SRI | Type | ECE |
|-------------|----------|--------|---------|---------|-----|-----|-----|------|-----|------|-----------------|
| 400/50 R 15 | STANDARD | 118 A8 | 13.00 | | 380 | 775 | 329 | 2269 | 370 | TL | E11-106R-009073 |
| 440/50 R 17 | STANDARD | 135 D | 14.00 | 13.00 | 441 | 872 | 395 | 2674 | 410 | TL | E4-106R-000662 |
| 500/50 R 17 | STANDARD | 147 D | 16.00 | | 490 | 940 | 425 | 2850 | 450 | TL | E11-106R-007767 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/4/2024 1:33 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..