

VIJETA - Technical Specifications



Description

VIJETA is an agricultural tire suitable for both on- and offthe-road applications. The 5-rib pattern optimizes load distribution. In addition, the wear-resistant compound and the strong casing stand for a long tire life-cycle.

UM

US Standard

Construction



Machinery

Agriculture: Trailer

| Version | STANDARD |
|-----------|-----------|
| Туре | ΤΤ |
| Tyre Size | 7.00 - 19 |

Dimensions US Standard

| Usa code | 94045099 |
|-------------------------|-----------------|
| Ply Rating | 10 |
| Section Width (inch) | 7.7 |
| Overall Diameter (inch) | 33.5 |
| Rim Rec | 5.00 |
| ECE | E11-106R-004106 |

Load capacity (lbs)

| mph / psi | 75 |
|-----------|------|
| 10 | 3000 |

Printed on 4/19/2024 11:04 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..