

## XL GRIP IND3 (RTG) - Technical Specifications



### Description

XL GRIP (IND-3) is a bias-ply tire for RTG cranes in stacking and lifting applications. The tire features a strong casing made of a specially formulated tread compound, which provides an extended tire life-cycle.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: RTG Crane

Version	INDUSTRIAL
Type	TL
Tyre Size	16.00 - 25

# Dimensions International Standard

Ply Rating	32
Overall Width (mm)	465
Overall Diameter (mm)	1485
Static Loaded Radius (mm)	682
Rolling Circumference (mm)	4395
Rim Rec	11.25/2.0
Rim Alt	13.00/2.0
TRA Code	IND3

## Load capacity (Kg)

km/h / bar	10.00
10	16875

Printed on 3/20/2024 9:51 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..