XL GRIP PLUS - Data Sheet

Description

XL GRIP PLUS (L-4) has been specially designed for loaders. Its deep tread provides high cut and puncture resistance as well as an extended tire life-cycle. XL GRIP PLUS is particularly suitable for heavy-duty service.

UM

US Standard

Construction

BIAS

Machinery

OTR: Dozer • Loader

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
26.5 - 25	STANDARD	94033331	L4	28	22.00/3.0		27.2	69.9	32.1	206.8	TL
26.5 - 25	STANDARD	94044856	L4	32	22.00/3.0		27.2	69.9	32.1	206.8	TL
29.5 - 25	STANDARD	94033584	L4	28	25.00/3.5		29.9	75.4	34.5	224.8	TL
29.5 - 25	STANDARD	94044863	L4	32	25.00/3.5		29.9	75.4	34.5	224.8	TL
29.5 - 25	STANDARD	94059577	L4	36	25.00/3.5		29.9	75.4	34.5	224.8	TL
35/65 - 33	STANDARD	94064762	L4	42	28.00/3.5		35.4	81.9	0	0	TL

Printed on 4/16/2024 8:56 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..