

# XL GRIP (SCRAPER) - Data Sheet



## **Description**

XL GRIP (SCRAPER) is a non-directional wide-base tire, particularly suitable for scrapers on any terrain. The tire features a strong casing and a special tread compound providing high cut and puncture resistance as well as excellent durability and traction even during heavy-duty operations. Additional features are best self-cleaning properties and exceptional stability.

#### **UM**

International Standard

### Construction



# Machinery

**OTR: Scraper** 

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	Туре
29.5 - 29	STANDARD	E3	28	25.00/3.5	26.00/3.5	760	1965	TL
33.25 - 29	STANDARD	E3	32	27.00/3.5	26.00/3.5	862	2120	TL
33.25 - 35	STANDARD	E3	32	27.00/3.5	29.00/3.5	862	2270	TL
33.25 - 35	STANDARD	E3	38	27.00/3.5	29.00/3.5	862	2270	TL
37.25 - 35	STANDARD	E3	36	31.00/4.0	29.00/3.5	955	2364	TL
37.5 - 39	STANDARD	E3	52	32.00/4.5		975	2570	TL

#### Printed on 4/20/2024 3:59 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..